

DIGITAL CAMERA		PowerShot SX510 HS
<b>IMAGE SENSOR</b>		
Type	1/2.3 type back-illuminated CMOS	
Effective Pixels	Approx. 12.1M	
Colour Filter Type	Primary Colour	
<b>IMAGE PROCESSOR</b>		
Type	DIGIC 4 with iSAPS technology	
<b>LENS</b>		
Focal Length	4.3 – 129.0 mm (35 mm equivalent: 24 – 720 mm)	
Zoom	Optical 30x ZoomPlus 60x Digital Approx. 4x (with Digital Tele-Converter Approx. 1.5x or 2.0x and Safety Zoom [1]). Combined Approx. 120x	
Maximum f/number Construction	f/3.4 – f/5.8 13 elements in 10 groups (1 UD lens, 1 double-sided aspherical lens)	
Image Stabilisation	Yes (lens shift-type), approx. 2.5-stop [13]. Intelligent IS plus Enhanced Dynamic IS	
<b>FOCUSING</b>		
Type	TTL	
AF System/Points	AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)	
AF Modes	Single, Continuous, Servo AF/AE[6], Tracking AF	
AF Point Selection	Size (Normal, Small)	
AF Lock	On/Off Selectable	
AF Assist Beam	Yes	
Manual Focus	Yes	
Closest Focusing Distance	0 cm (W) from front of lens in macro	
<b>EXPOSURE CONTROL</b>		
Metering modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (Centre)	
AE Lock	Yes	
Exposure Compensation	+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction	
ISO sensitivity	AUTO, 100, 200, 400, 800, 1600, 3200	
<b>SHUTTER</b>		
Speed	1 – 1/1600 sec. (factory default) 15 – 1/1600 sec. (total range – varies by shooting mode)	
<b>WHITE BALANCE</b>		
Type	TTL	
Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom	
<b>LCD MONITOR</b>		
Monitor Coverage Brightness	7.5 cm (3.0”) TFT, Approx. 461,000 dots Approx. 100% Adjustable to one of five levels. Quick-bright LCD	
<b>FLASH</b>		
Modes	Auto, Manual Flash On / Off, Slow Synchro	
Slow Sync Speed	Fastest speed 1/1600 sec.	
Red-Eye Reduction	Yes	
Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments. Face Detection FE. Safety FE, Smart Flash Exposure	
Flash Exposure Lock	Yes	
Manual Power Adjustment	3 levels with internal flash	
Built-in Flash Range	50 cm – 5.0 m (W) / 50 cm – 3.0 m (T)	
External Flash	Canon High Power Flash HF-DC2	

SHOOTING	
Modes	Smart Auto (32 scenes detected), Movie Digest, Program AE, Shutter priority AE, Aperture priority AE, Manual, Live View Control, SCN (Portrait, FaceSelf-Timer, Low Light (3.0MP), Snow, Fireworks), Creative Filters (Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect), Discreet, Movie
Modes in Movie	Smart Auto (21 scenes detected), Standard, Program AE, Portrait, Snow, Fireworks, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Super Slow Motion Movie
Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
Drive modes	Single, Continuous, Continuous with AF, Self-Timer
Continuous Shooting	Approx. 3.8 shots/sec High-speed Burst (3MP): 10.5 shots/sec with AF: Approx. 1.0 shots/sec. with Live View: Approx. 1.0 shots/sec (all speeds are until memory card becomes full)[3][4]
RECORDING PIXELS / COMPRESSION	
Image Size	4:3 - (L) 4000 x 3000, (M1) 2816 x 2112, (M2) 1600 x 1200, (S) 640 x 480 16:9 - (L) 4000 x 2248, (M1) 2816 x 1584, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 4000 x 2664, (M1) 2816 x 1880, (M2) 1600 x 1064, (S) 640 x 424 1:1 - (L) 2992 x 2992, (M1) 2112 x 2112, (M2) 1200 x 1200, (S) 480 x 480
Compression Movies	Resize in playback (M2, S) Superfine, Fine (Full HD) 1920 x 1080, 24 fps, (HD) 1280 x 720, 30 fps, (L) 640 x 480, 30 fps Super Slow Motion Movie (L) 640 x 480, 120fps, (M) 320 x 240, 240fps Miniature Effect (HD, L) 6fps, 3fps, 1.5 fps Movie Digest (L)
Movie Length	(Full HD & HD) Up to 4 GB or 29 min. 59 sec. [7] (L) Up to 4 GB or 1 hour [4] (Super Slow Motion Movie) 30 sec.
FILE TYPES	
Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
Movies	MOV [H.264 + Linear PCM (stereo)]
DIRECT PRINT	
Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
PictBridge	Yes (via USB or Wireless LAN)
OTHER FEATURES	
GPS	GPS via mobile (linked to compatible smartphone)
Red-Eye Correction	Yes, during shooting and playback

	My Category Intelligent Orientation Sensor Histogram Playback zoom Self Timer Menu Languages	Image tagging feature Yes  Yes Approx. 2x – 10x Approx. 2 or 10 sec., Custom English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese
<b>INTERFACE</b>		
	Computer	Hi-Speed USB (MTP, PTP) dedicated connector (Mini-B compatible)
	Other	HDMI Mini Connector (HDMI-CEC compatible) A/V output (PAL/NTSC)
	Computer/Other	Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only) [11]
<b>MEMORY CARD</b>		
	Type	SD, SDHC, SDXC
<b>SUPPORTED OPERATING SYSTEM</b>		
	PC & Macintosh	Windows 8/7 SP1/ Vista SP2/ XP SP3 Mac OS X v10.6 – 10.8  For Wireless LAN connection to a PC: Windows 8/7 SP1 Mac OS X v10.6.8/10.7/10.8.2 or later
<b>SOFTWARE</b>		
	Browsing & Printing Other	ImageBrowser EX PhotoStitch, Map Utility
<b>POWER SOURCE</b>		
	Batteries	Rechargeable Li-ion Battery NB-6LH (battery and charger supplied)
	Battery life	Approx. 250 shots Eco mode approx. 330 shots Approx. 300 min. playback
	A/C Power Supply	Optional, AC Adapter Kit ACK-DC40
<b>ACCESSORIES</b>		
	Cases / Straps Flash Power Supply & Battery Chargers	Soft Case DCC-970, DCC-950 Canon High Power Flash HF-DC2 AC Adapter Kit ACK-DC40, Battery Charger CB-2LYE
	Other	Canon HDMI Cable HTC-100, interface cable IFC- 400PCU
<b>PHYSICAL SPECIFICATIONS</b>		
	Operating Environment Dimensions (WxHxD) Weight	0 – 40 °C, 10 – 90% humidity 104.0 x 69.5 x 80.2 mm Approx. 349 g (including battery/batteries and memory card)

**All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.**

**Subject to change without notice.**

**[1] Depending on the image size selected.**

**[3] Under conditions where the flash does not fire.**

**[4] Depending on memory card speed / capacity / compression setting.**

**[6] Some settings limit availability.**

**[7] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.**

**[11] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit [www.canon-europe.com/wirelesscompacts](http://www.canon-europe.com/wirelesscompacts)**

**[13] Values at maximum optical focal length. Cameras whose focal length exceeds 350mm (35mm equivalent) are measured at 350mm.**